

Technical Specifications

Model a526d	DY070A
Processor & Speed	2.6 GHz/400 Intel® Pentium® 4 Processor – PGA478
Chipset	Intel® 845GV
Motherboard	Gamilla2-GL6E (MS-6577)
RAM	256/2700 MB 333DDR SDRAM (runs@266 MHz)
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	8KB Data Cache + Trace Cache L1, 512 KB L2 Integrated on Processor module
Hard Drive	40 GB (5400 RPM)
Optical Drive	CD-RW Drive: 48x-Write / 24X-Re-write/CD-ROM speed =48x max.
Average Random Access	110ms
Transfer Rate	6.0MB/sec.
Diskette Drive	3.5" (1.44MB)
Fax/Data Modem	V.90 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
Video Graphics	Intel® Extreme Graphics
Controller	Integrated w/845G Chipset
Video Memory	Dynamic up to 64MB UMA
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC658
Chassis	Panther-Lite, 250HV PSU
USB Interface Specification	USB 2.0
External I/O Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
External I/O Front Connectors	2=USB, 1= 1394, Line In, Microphone, Headphone
Expansion Slots (Total)	3= PCI
Expansion Slots (FREE)	2= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2004
This information is subject to change without notice and is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.